

## Billerud Pure Performance LINER

### Product Description

Pure Performance is a white top kraftliner produced from 100% virgin fibres. The characteristics for this grade are high and consistent quality combined with superior runnability.

### Grammages

135, 160, 175 g/m<sup>2</sup>

### Approvals

Pure Performance is produced in compliance with FDA and BfR packaging norms.

### Certification

Production is certified in accordance with ISO 9001, ISO 14001, ISO 50001 and FSSC 22000.

Property	Unit		Method			
Grammage	g/m <sup>2</sup>	135	160	175	ISO 536	
Caliper	µm	165	195	215	ISO 534	
Air resistance	s	80	90	100	ISO 5636-5	
Scott Bond	J/m <sup>2</sup>	350	350	350	TAPPI T569	
Burst strength	kPa	640	770	850	ISO 2758	
SCT	CD	kN/m	3,1	3,6	4,0	ISO 9895
Tensile	MD	kN/m	1400	1550	1700	ISO 1924
	CD	kN/m	500	650	700	
Roughness	PS	ml/min	290	350	370	ISO 8791-2
Brightness	PS	%	75	75	75	ISO 2470
Cobb	PS	g/m <sup>2</sup>	26	26	26	ISO 535
	RS	g/m <sup>2</sup>	40	40	40	
Moisture	%	8,0	8,0	8,0	ISO 287	

MD = Machine Direction   CD = Cross Direction   PS = Print Side   RS = Reverse Side   Test climate: 50% RH, 23°C

The table shows typical data for a range of grammages.

Rev. 202301