

Pure Decor™
LINER

Product Description

The light coated Pure Decor™ kraftliner is a preferred material for high quality post-print and pre-print. High strength ensures light, strong packages with minimised washboarding. Pure Decor™ is produced from 100% virgin fibres.

Grammages

30, 33, 36 lbs/1000ft²
(145, 160, 175 g/m²)

Approvals

Pure Decor™ is produced in compliance with FDA and BfR packaging norms.

Certifications

Production is certified in accordance with ISO 9001, ISO 14001 and FSSC 22000.

Property	Unit		Method		
Grammage	lbs/1000ft ² (g/m ²)	30 (145)	33 (160)	36 (175)	ISO 536
Thickness	in/1000	7,1	7,7	8,3	ISO 534
Scott Bond	ft.lbs/1000in ²	167	167	167	TAPPI T569
Burst strength	Psi	105	113	122	ISO 2758
SCT	CD lbf/in	18,3	20,5	22,8	ISO 9895
Tensile Stiffness	MD lbf/in CD lbf/in	7130 3420	7420 3990	7990 4560	ISO 1924
Roughness PPS-10	PS Microns	1,4	1,5	1,6	ISO 8791-4
Gloss	PS %	45	45	45	ISO 8254-1
Brightness	PS %	80	80	80	ISO 2470
Whiteness D65	PS %	82	82	82	ISO 11475
Cobb	PS lb/1000ft ² RS lb/1000ft ²	7,0 7,8	7,0 7,8	7,0 7,8	ISO 535
Moisture	%	7,0	7,0	7,0	ISO 287

MD = Machine Direction

CD = Cross Direction

Test climate: 50% RH, 23°C

Rev. 202201

The table shows typical data for a range of grammages.