

Cartonboard sales contacts

Nordic

Cartonboard.nordic@billerud.com

UK

Cartonboard.UK@billerud.com

Germany, Austria & Switzerland

Cartonboard.DACH@billerud.com

France, Spain & Portugal

Cartonboard.FranceSpainPortugal@billerud.com

Mediterranean Region

Cartonboard.Mediterraneanregion@billerud.com

Benelux

Cartonboard.Benelux@billerud.com

North America

Cartonboard.NorthAmerica@billerud.com

Eastern Europe

Cartonboard.EasternEurope@billerud.com

Over Seas

Cartonboard.OverSeas@billerud.com

We make high performance packaging
materials for a low carbon society

CrownBoard **Carry**

Technical specifications

CrownBoard Carry is a multi-ply board made from 100% fresh fibers offering exceptional strength and tear resistance. It features a fully coated top side for excellent printability and a brown reverse side that adds a natural, rustic appeal and design flexibility. CrownBoard Carry is the ideal choice for multipacks and other heavy-duty applications where strength is critical. Its high strength also makes it excellent for lightweighting - or when extra durability is needed without adding weight.

CrownBoard Carry

CrownBoard Carry is a multilayer, coated, unbleached kraft back board made from 100% strong, fresh fibers – designed for multipacks and produced in Sweden.

DECLARATION OF CONTENTS

- Coated top side
- Top: Bleached chemical pulp
- Middle: CTMP, reinforced with unbleached chemical pulp – a unique combination of flexibility, strength and stiffness
- Bottom: Unbleached chemical pulp



Property	Unit					Method
Caliper	pt	16	17	18	20	
Thickness	µm	406	432	457	508	ISO 534
Basis weight	g/m²	250	275	290	320	ISO 536
Bending resistance L&W 15° MD	mN	360	440	540	710	ISO 2493
	CD mN	160	200	240	320	ISO 2493
Tearing resistance (dry)	GM mN	4500	5000	5500	6500	ISO 1974
Brightness, D65	PS %	77	77	77	77	ISO 2470-2

The table shows *indicative* data.

CERTIFICATION

Our mills are certified in accordance with ISO 9001, ISO 14001, ISO 50001, FSSC 22000. PEFC CoC and FSC® CoC Certification is available. The product is in compliance with FDA and BfR regarding food contact applications. For restriction and limitations, ask your Billerud sales representative. Recyclable in accordance with EN 13430:2004 and EN 13431:2004.

- Values may be subject to change without notice.
- Testing climate 23°C, 50% RH.
- Billerud production units are certified according to FSC® and PEFC Chain of Custody standards, which both demonstrate traceability. License codes: FSC-C004906 and PEFC/05-33-114.
- FSC® and PEFC certified products are available on request.
- Min/max property values are lower resp. upper limit values for 95% confidence interval of the tested properties and are based on measurements on tambour basis.
- Bending stiffness values may be negatively influenced during the converting process.