BILLERUDKORSNÄS

Technical data sheet

Date: November 2019

Basix Repel 5R Plus WHITE MG KRAFT PAPER

Production Unit: Beetham

End uses

Basix Repel 5R Plus is a grease resistant paper treated on one side only, (Non MG side). Basix Repel 5R Plus is especially suitable for further lamination or coating on the untreated side. Basix Repel 5R Plus is suitable for direct contact with food containing grease and oil. Can be printed, corrugated and embossed.

Grammage

60 g/m²

Materials

Basix Repel 5R Plus is produced from pure, white Kraft pulp and consists entirely of virgin fibre. Basix Repel 5R Plus is produced with non-telomer fluorochemical.

Printing method Flexography

Approvals

Basix Repel 5R Plus is produced in compliance with relevant sections of BfR and FDA food packaging regulations.

Certification

Basix Repel 5R Plus is produced at BillerudKorsnäs Beetham, which is certified in accordance with ISO 9001, ISO 14001, BS OHSAS18001 and ISO 22000

Property	Unit			Method
Grammage	g/m ²		60	On Line QCS
Tensile strength	N/15mm	MD CD	96 56	ISO 1924-3
Tear strength	mN	MD CD	385 435	ISO 1974
Burst strength	kPa		300	ISO 2758
Porosity Bendtsen	ml/min		75	ISO 5636-3
Porosity Gurley	S		159	ISO 5636-3*
Water Absorbance Cobb 60s	g/m²	MG	28	ISO 535
Grease/Oil Resistance	Kit Test	RS	5-6	ISO16532-2

MD = Machine Direction CD = Cross Direction MG = MG side RS = Reverse Side Test climate: 50% RH, 23C Issue: 3 Rev:1 2019-11

The table shows typical values.

* indicates derived value, for information only.